Cast Iron

Sprinkler Pumps

Rugged Pump Housing
Durable, cast iron construction

Superior Performance
At depths to water of 25' or less

High Capacity
Ideal for larger sprinkler zones or water transfer

Heavy-Duty Dual-Voltage Motor
Preset at 230V

Self-Priming After Pump Housing Is Initially Filled
Check valve or foot valve required, sold separately

Drain Port Provided
For convenient winterizing

1-Year Warranty



2 HP 64 GPM FP5252

1-1/2 HP 55 GPM FP5242

PERFORMANCE

MODEL/UPC	HP	GPM	VOLTS	DISTANCE OF PUMP ABOVE WATER	DISCHARGE PRESSURE (PSI)							NPT PIPE SIZE		CARTON DIMS. (IN INCHES)	WT. (LBS.)
					20	25	30	35	40	45	50	SUCTION	DISCH.		
FP5252 022315162808	**2**	**64**	230/115	5'	64	58	53	45	38	28	19	2"	2"	24.063 x 17.938 x 13.563 12/PALLET	86.2
				10'	62	56	50	42	35	24	13				
				15'	59	53	47	39	31	20	-				
				20'	57	50	44	35	26	-	-				
				25'	51	44	38	30	20	-	-				
FP5242 022315162792	**1-1/2**	**55**	230/115	5'	55	50	45	28	31	20	-	2"	1-1/2"	24.063 x 17.938 x 13.563 12/PALLET	71.4
				10'	53	47	42	34	27	16	-				
				15'	51	45	39	30	22	-	-				
				20'	49	42	36	27	18	-	-				
				25'	46	39	32	22	12	-	-				

Includes:
Threaded ports for pressure gauge and drain plug, detailed owner's manual