PRODESEG S.A.
DISTRIBUIDOR AUTORIZADO
www.prodeseg.com.co



G-Force Selectable One-Piece Nozzle With Pistol Grip, Slide Valve - 30/60/95/125/150 GPM @ 100 PSI, 1.5" NHF Rocker Swivel Inlet, Spinning Metal Teeth, Fixed Shaper Indicator

Tailored Performance

Categories: Handline Nozzles

G-Force® Selectable nozzles allow firefighters to switch between multiple flow settings, adapting quickly to specific fireground requirements. Available in various inlet sizes, the G-Force® Selectable nozzles offer intuitive control with a tactile shaper indicator and durable build for enhanced reliability. Ideal for crews seeking precise water control with the flexibility to adjust flows as needed, these nozzles support advanced firefighting tactics in any situation.

Key Features:

- **Multiple Flow Settings**: Choose from various flow rates to match firefighting demands, up to 150 GPM (570 LPM)
- **Slide Valve Control**: High-quality valves for smooth, responsive adjustments
- **Customizable Fog Teeth**: Options include fixed rubber, spinning metal, or fixed cut metal
- **Pattern Selector**: Tactile shaper indicator for intuitive stream pattern selection

Task Force Tips

SKU: GF3C1S

- **Hard Anodized Body**: Lightweight aluminum body for ease of handling and corrosion resistance
- **Pistol Grip & Trigger Options**: Available with ergonomic grip styles for better maneuverability and triggers for advanced firefighting tactics
- **Reflective Markings**: Increases visibility of operational markings in all conditions
- **Enhanced Safety**: Bonded rubber bumper for durability and improved safety during intense use

Task Force Tips

SKU: GF3C1S

Specifications

Weight	4.500 lbs
Color	Black
Brand	G-Force®
Nozzle Type	Selectable
Nozzle Valve Style	Slide Valve
Nozzle Teeth	Spinning Metal
Certifications	NFPA/FM
Nozzle Style	1-Piece
Nozzle Grip	Pistol
Target Nozzle Flow (Imp)	30/60/95/125/150 GPM
Target Nozzle Flow (Met)	110/230/360/470/570 LPM
Target Nozzle Pressure (Bar)	7 Bar
Nozzle Hose Size (Imp)	1.5"
Nozzle Hose Size (Met)	38 mm
Nozzle Hose Connection Type	NH Female
Nozzle Hose Coupling Style	Rocker Lugs
Nozzle Hose Coupling Swivel	Swivel
Nozzle Shaper Indicator	Fixed Shaper Indicator
Target Nozzle Pressure (PSI)	100 PSI
Target Nozzle Pressure (KPA)	700 KPA

Documents

Certifications & Approvals

- 1.5" G-Force NFPA 1960
- G-Force Series FM Approval

Task Force Tips

SKU: GF3C1S

Instructions For Installation, Safe Operation and Maintenance

- G-Force Manual: Fixed & Selectable and Automatic