UL Product iQ®

Model FCA 65, FCA-S 65

File Number: EX16058

COMPANY

HD FIRE PROTECT PVT LTD
K-98, MIDC
AJANTA RD
JALGAON, Maharashtra 425003 India

MODEL INFO

FCA 65, FCA-S 65
Foam chamber

THE FOLLOWING ARE DISCHARGE RATES FOR THE DEVICE INLET PRESSURES:

Inlet Pressure Range, psi (kPa)	Flow Range, gpm (L/min)	Orifice Diam Range, in. (mm)	C - "Constant" (refer to Guide Info)
30-100	35.40- 149.80	0.590 - 0.902	

GENERAL

Installation Notes

Refer to the individual foam concentrate Listings for operating limitations with specific combinations of foam concentrates and discharge outlets.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."