UL Product iQ™

VLFT.EX2834 - SPECIAL SYSTEM WATER CONTROL VALVES, DELUGE TYPE

Special System Water Control Valves, Deluge Type

See General Information for Special System Water Control Valves, Deluge Type

GRISWOLD INDUSTRIES, DBA CLA-VAL CO EX2834
1701 PLACENTIA AVE
COSTA MESA, CA 92627-4416 USA

Deluge valves, Models 100G and 100GS, nominal pipe size 3, 4, 6, 8, 10 and 12 NPS, flanged end configuration, globe type, and Models 100G and 100GS, nominal pipe size 3, 4, 6 and 8 NPS, grooved end configuration, globe type intended for horizontal or vertical installation with a pressure rating of 300 psig. For operation manually, electrically, pneumatically and by wet pilot line of sprinklers utilizing the 134-05 trim configuration.

Deluge valves, Model 134-83 and 134-83KX, nominal pipe size, 4 and 6 NPS, flanged and grooved end configurations, globe type, intended for horizontal or vertical installation positions with an inlet pressure rating of 300 psig. For operation manually, electrically and by wet pilot line sprinklers all with pressure reducing feature. Pressure reducing outlet setting pressure range is 50-165 psig for the 4 NPS valve. Pressure reducing outlet setting pressure ranges are 35-90 psig and 50-165 psig for the 6 NPS valve.

Deluge valves, Models 2100G and 2100GS, nominal pipe size 3, 4, 6, 8, 10 and 12 NPS, flanged end configuration, angle type, intended for horizontal or vertical installation with a pressure rating of 300 psig. For operation manually, electrically, pneumatically and by wet pilot line of sprinklers utilizing the 134-05 trim configuration.

Deluge valves, Model 8134-05, nominal pipe size 2, 2-1/2, 3, 4, 6, and 8 NPS, flanged and grooved end configurations, globe type, intended for horizontal or vertical installation with a pressure rating of 200 psig utilizing the 134-05 trim configuration. For Electric Release.

For operation by wet pilot line sprinklers, height of pilot line above the valve to be limited as shown in the Installation Instructions.

For accessories used with these valves, see Listing under "Accessories for Special Systems".

Last Updated on 2018-08-17

La presencia del nombre de una empresa o producto en esta base de datos no garantiza por sí misma que los productos así identificados hayan sido fabricados bajo el servicio de seguimiento de UL. Solo aquellos productos que lleven la marca UL deben considerarse como certificados y garantizados bajo el servicio de seguimiento de UL. Busque siempre la marca en el producto.

UL permite la reproducción del material contenido en el directorio de certificación en línea sujeta a las siguientes condiciones: 1. La información de la guía, las asambleas, las construcciones, los diseños, los sistemas y/o certificaciones (archivos) deben presentarse en su totalidad y de forma no engañosa, sin ninguna manipulación en los datos (o dibujos). 2. Debe aparecer la declaración "Reimpreso desde el directorio de certificaciones en línea con permiso de UL" junto al material extraído. Además, el material reimpreso debe incluir una nota de derechos de autor en el siguiente formato: "© 2019 UL LLC"

PRODESEG S.A.
DISTRIBUIDOR AUTORIZADO
www.prodeseg.com.co