Monitors

FM Approved monitors are specially designed with large clear waterways to give a powerful, far-reaching stream for the protection of pulpwood piles, lumber yards or other locations where a large amount of water must be instantly available without the delay of laying hose lines.

Hurricane XFI-FLNJ...

Hurricane Series. Rated to 1250 gpm (4500 Lpm), with a maximum operating pressure of 250 psi (17 bar).

Series	*Designation*	*Material*	*Inlet*	*Outlet**
Hurricane	XFI-FLNJ	Aluminum	3 in. ANSI 150 flange	2.5 in. NH
Hurricane	XFI-FPNJ	Aluminum	4 in. ANSI 150 flange	2.5 in. NH
Hurricane	XFI-PLNJ	Aluminum	3 in. NPT female	2.5 in. NH
Hurricane Extended	XFIE-FPNJ	Aluminum	3 in. ANSI 150 flange	2.5 in. NH
Hurricane Extended	XFIE-FPNJ	Aluminum	4 in. ANSI 150 flange	2.5 in. NH

*2.5 in. BSP outlets are also available.

Company Name:	Task Force Tips Inc
Company Address:	2351 Industrial Dr, Valparaiso, Indiana 46383, USA
Company Website:	http://tft.com
New/Updated Product Listing:	No
Listing Country:	United States of America
Certification Type:	FM Approved
Class of Work:	1421-Monitor Nozzles

© 2007-2019 FM Approvals. All rights reserved.