

PU Lining Hose
color:

Rack-U, Sintack-U

Jacket: 100% Virgin Polyester Jacket, Single Jacket, Twill or Plain Weave.

Lining: Polyurethene (PU) tube

Application: Rack hose, Cabinet Hose, Premium solution.

Standard length: 15m (50ft), 20m (66ft), 22.5m (75ft), 30m (100ft)

I.D.		Service Pressure	Minimum Burst Pressure
inch	mm	psi/bar	psi/bar
1 1/2"	40	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
1 3/4"	45	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
2"	50	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
2 1/2"	65	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51



EPDM Lining Hose
color:

Rack-D, Sintack-D

Jacket: 100% Virgin Polyester Jacket, Single Jacket, Twill or Plain Weave.

Lining: EPDM rubber tube, vulcanized twice

Application: Industrial Fire Fighting, Fire hose for brigade, Premium Solution.

Standard length: 15m (50ft), 20m (66ft), 25m (82ft), 30m (100ft)

I.D.		Service Pressure	Minimum Burst Pressure
inch	mm	psi/bar	psi/bar
1 1/4"	32	150/10, 200/14, 220/15, 250/17, 300/21	450/30, 600/42, 660/45, 750/51, 900/63
1 1/2"	40	150/10, 200/14, 220/15, 250/17, 300/21	450/30, 600/42, 660/45, 750/51, 900/63
1 3/4"	45	150/10, 200/14, 220/15, 250/17, 300/21	450/30, 600/42, 660/45, 750/51, 900/63
2"	50	150/10, 200/14, 220/15, 250/17, 300/21	450/30, 600/42, 660/45, 750/51, 900/63
2 1/2"	65	150/10, 200/14, 220/15, 250/17, 300/21	450/30, 600/42, 660/45, 750/51, 900/63
2 3/4"	70	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
3"	75	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51

*All above technical parameters are for reference, details please confirm with ZYfire.

Attack Hose



PU Lining Hose

color:

Twintack-U

Jacket: 100% Virgin Polyester Jacket, Double Jacket, Twill or Plain Weave. High Performance in abrasion resistance.

Lining: PU tube

Application: Industrial Fire Fighting, Fire hose for brigade, Premium solution.

Standard length: 15m (50ft), 20m (66ft), 25m (82ft), 30m (100ft)

I.D.		Service Pressure	Minimum Burst Pressure
inch	mm	psi/bar	psi/bar
1 1/4"	32	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
1 1/2"	38	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
1 3/4"	45	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2"	50	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2 1/2"	65	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2 3/4"	70	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
3"	75	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
4"	102	300/21	900/63
6"	152	300/21	900/63



EPDM Lining Hose

color:

Twintack-D

Jacket: 100% Virgin Polyester Jacket, Double Jacket, Twill or Plain Weave. High performance in abrasion resistance.

Lining: EPDM rubber tube

Application: Industrial Fire Fighting, Fire hose for brigade, Premium solution.

Standard length: 15m (50ft), 20m (66ft), 25m (82ft), 30m (100ft)

I.D.		Service Pressure	Minimum Burst Pressure
inch	mm	psi/bar	psi/bar
1 1/4"	32	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
1 1/2"	38	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
1 3/4"	45	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2"	50	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2 1/2"	65	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
2 3/4"	70	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
3"	75	250/17, 300/21, 400/28	750/51, 900/63, 1200/84
4"	102	300/21	900/63
5"	127	300/21	900/63
6"	152	300/21	900/63

*All above technical parameters are for reference, details please confirm with ZYfire.

Attack Hose



Nitrile Rubber Covered Hose

color:

Lexus Hose

Reinforcement: Synthetic yarn

Cover and Tube: Nitrile/TPR blend tube, thin rib on cover provides better performance in abrasion resistance.

Application: Large diameter hose for water supply, Municipal, Industrial Fire Fighting, Premium Solution.

I.D.		Service Pressure	Minimum Burst Pressure
inch	mm	psi/bar	psi/bar
1 1/4"	32	200/14, 220/15, 250/17, 300/21, 400/28	600/42, 660/45, 750/51, 900/63, 1200/84
1 1/2"	38	200/14, 220/15, 250/17, 300/21, 400/28	600/42, 660/45, 750/51, 900/63, 1200/84
1 3/4"	45	200/14, 220/15, 250/17, 300/21	600/42, 660/45, 750/51, 900/63
2"	51	200/14, 220/15, 250/17, 300/21	600/42, 660/45, 750/51, 900/63
2 1/2"	65	200/14, 220/15, 250/17, 300/21	600/42, 660/45, 750/51, 900/63
2 3/4"	70	200/14, 220/15, 250/17, 300/21	600/42, 660/45, 750/51, 900/63
3"	78	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
4"	102	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
4 1/2"	115	150/10, 200/14, 220/15, 250/17	450/30, 600/42, 660/45, 750/51
5"	127	120/8, 150/10, 200/14	360/24, 450/30, 600/42
5 1/2"	140	120/8, 150/10, 200/14	360/24, 450/30, 600/42
6"	154	120/8, 150/10, 200/14	360/24, 450/30, 600/42
7 1/4"	184	120/8, 150/10	360/24, 450/30
8"	204	120/8, 150/10	360/24, 450/30
10"	254	120/8	360/24
12"	306	120/8	360/24





*All above technical parameters are for reference, details please confirm with ZYfire.